



Quantum

ALL-IN-ONE MultiTouch POS Terminal



Specification		QS-525	QX-1900
CPU Support	Intel Pineview D525 processors 1.8GHz		Intel Bay Trail- D J1900 2G, L2 2M
System Memory	DDR3, SO-DIMM x 1, 2GB (Max. 4GB)		DDR3L, SO-DIMM x 2, 2GB (Max. 8GB)
OS Support	Windows 7 Professional Windows Embedded POSReady 7 Linux		Windows 7 Professional Windows Embedded POSReady 7 Linux / Windows 8.1
Storage			
HDD	320GB 2.5"x 1		
SSD	SSD x 1 (Optional)		
LCD			
Size/Resolution	15" TFT LED LCD Panel/1024 x 768		
Brightness	350cd/m2 (Typ.)		
Touch Screen	True-Flat Projected Capacitive Touch		
Tilt Angle	0 ~ 120 degree		
External I/O Port			
Rear	3 x Serial port (RJ45); (COM1~2: 0/5/12V by BIOS; COM3:0/5V by BIOS)	3 x Serial port (RJ45); (COM1~3: 0/5/12V by BIOS)	
	1 x VGA (Power enable by BIOS; +12V)		
	1 x Cash Drawer Port (RJ11; +12V)		
	1 x Mic-In/Speaker-out (Combo Jack)		
	1 x LAN (10/100/1000)		
	1 x DC In		
	1 x Power Switch		
Power			
EMC Safety	CE, FCC Class A		
Environment			
Operating /Storage Temperature	0°C ~ 35°C/ -20°C ~ 60°C		
Operating /Storage Humidity	20% - 85% RH non condensing		
Optional			
Wall Mount	VESA 100 x 100mm		
MSR (USB)	MSR/MSR + Finger Print (Combo)/MSR + iButton (Combo)/MSR + RFID (Combo)		
Customer display (USB)	Flush mount VFD display, 2x20 characters		
2nd Display	10" (1024 x 768)		
Speaker	2 x 2W speaker		



Web site: www.quripos.eu

E-mail: info@quripos.eu